

Marine Hatch Hinge

Now there is a no-compromise hatch hinge that is elegant and practical in design. Easily installed and rugged, you can have complete confidence in a watertight and secure fitting.

Made entirely from 316 stainless steel, the Marine Hatch Hinge is flush mounted and will recess into your deck to give a clean stylish finish. The hinge is secured from below deck so no fasteners are visible from above. The securing bolt thread in the hinge is 'SecuraLock' which accepts standard thread bolts without the need for spring washers so you can use counter-sunk bolts for a flush under-deck installation.

Specifications

| | |
|-----------------------------------|---|
| Construction material | 316 stainless steel |
| Hole size | 31.75 mm (1 1/4") |
| Depth of hole | 22 mm (7/8") |
| Distance between mounting centres | 80 mm (3 3/16") |
| Hinge bar slot size | 12.75 mm x 12.75 mm (1/2" x 1/2") |
| Securing bolts | M8 standard, others to order |
| Included accessories | Two countersunk 316 stainless steel bolts |



JEC e-mail updates – For your free e-mail newsletter subscription and product updates visit www.energyconversions.com.au. Learn about new developments designed to enhance your boating experience as a builder or an owner.

Jindra Energy Conversions Pty Ltd

Unit 26, 137–145 Rooks Road, Nunawading, VIC 3131 Australia. Phone: +61 3 8872 6555 Fax: +61 3 8872 6550

Email: info@energyconversions.com.au Website: www.energyconversions.com.au